

ATV630D15N4Z

Schneider Electric ATV630D15N4Z - Altivar Process ATV630 Variable Speed Drive 15 kW

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	ATV630D15N4Z
PRODUCT FAMILY	CATEGORY
Altivar Process ATV600	VFD
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

This Altivar Process ATV600 variable speed drive can feed 3-phase synchronous and asynchronous power motors. It features three built-in RJ45 communication ports as standard, 1 Ethernet port, and two serial ports. It works at a rated supply voltage from 380V to 480V AC. This drive saves up to 30% energy when on standby due to the innovative "Stop and Go" operation without additional costs. It is suitable for motors with a power rating of up to 15kW / 20hp for applications requiring slight overload (up to 120%). It is suitable for motors with a power rating of up to 11kW / 15hp for applications requiring significant overload (up to 150%). It weighs 13kg, and its dimensions are 195mm wide, 480mm high, and 225.5mm deep. This drive is focused on fluids management processing and energy saving; it offers extensive flexibility in water and wastewater, mining, minerals and metals, oil and gas, and food and beverage applications. Accessories (fan kit, graphic display terminal, etc.) and options (I/O expansion modules, communication modules, EMC input filters, etc.) are available with Altivar Process ATV600 drives, depending on the drive rating. It is designed to be mounted vertically on a wall (+/- 10 °). This new concept of drives meets the major needs of processes and utilities regarding equipment efficiency and total cost of ownership by supporting energy management, asset management, and the process's overall performance. Schneider Electric ATV630D15N4Z is the exact manufacturer

RECORDED SPECIFICATIONS

Network phases	3 phases
Safety function	STO (safe torque off) SIL 3
Supply frequency	50...60 Hz
Rated supply voltage	380...480 V
IP degree of protection	IP20
Manufacturer part number	ATV630D15N4Z
Motor power (heavy duty)	11 kW
Motor power (normal duty)	15 kW
Output current (heavy duty)	23.5 A
Output current (normal duty)	31.7 A

ADDITIONAL SPECIFICATIONS

Speed drive output frequency	0.1?500 Hz
------------------------------	------------

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.