

ATV650U07N4

Altivar Process ATV600 Variable Speed Drive ATV650U07N4 0.75kW/1HP 380-480V

|                                   |                                |
|-----------------------------------|--------------------------------|
| BRAND                             | ORDER CODE / PRODUCT REFERENCE |
| Schneider Electric                | ATV650U07N4                    |
| PRODUCT FAMILY                    | CATEGORY                       |
| Altivar Process ATV600            | VFD                            |
| SUPPLY BASIS                      | RECORD IDENTITY                |
| RFQ / on request - no stock claim | Catalog identity matched       |

PRODUCT DESCRIPTION

This Altivar Process ATV600 variable speed drive can feed 3-phase synchronous and asynchronous power motors. It features 3 built-in RJ45 communication ports as standard, 1 Ethernet port, 2 serial ports. It works at a rated supply voltage from 380V to 480V AC. This drive provides up to 30% energy saving when on standby due to the innovative ??Stop and Go??operation without additional costs. It is suitable for motors with power rating up to 0.75kW / 1hp for applications requiring slight overload (up to 120%). It is suitable for motors with power rating up to 0.37kW / 0.5hp for applications requiring significant overload (up to 150%). It weighs 10.5kg and its dimensions are, 264mm wide, 678mm high, 272mm deep. This drive is focused on fluids management processing and energy saving, it offers extensive flexibility in water and wastewater, mining, minerals and metals, oil and gas and food and beverage applications. Accessories (fan kit, graphic display terminal) and options (I/O expansion modules, communication modules, EMC input filters) are available with Altivar Process ATV600 drives, depending on the drive rating. It is designed to be mounted in vertical position (+/- 10 °) on a wall. This new concept of drives meets the major needs of process and utilities in terms of equipment efficiency and total cost of ownership by supporting the energy management, asset management and also the overall performance of the process. Schneider Electric ATV650U07N4 is the exact manufacturer re

RECORDED SPECIFICATIONS

|                     |                             |
|---------------------|-----------------------------|
| Depth               | 272 mm                      |
| Width               | 264 mm                      |
| Height              | 678 mm                      |
| Phases              | 3                           |
| Weight              | 10.5 kg                     |
| Cooling type        | Forced convection           |
| IP protection       | IP55                        |
| Safety function     | STO (safe torque off) SIL 3 |
| Output frequency    | 0.0001-0.5 kHz              |
| EMC filter category | C2/C3                       |

ADDITIONAL SPECIFICATIONS

|                                         |                              |
|-----------------------------------------|------------------------------|
| Switching frequency                     | 2-12 kHz adjustable          |
| Prospective line Isc                    | 50 kA                        |
| Rated supply voltage                    | 380-480 V                    |
| Manufacturer part number                | ATV650U07N4                  |
| Motor power (normal duty)               | 0.75 kW / 1 hp               |
| Line current (normal duty)              | 1.5 A (380 V), 1.3 A (480 V) |
| Nominal switching frequency             | 4 kHz                        |
| Apparent power (normal duty)            | 1.1 kVA (480 V)              |
| Speed drive output frequency            | 0.1-599 Hz                   |
| Continuous output current (normal duty) | 2.2 A (4 kHz)                |
| Maximum transient current (normal duty) | 2.4 A (60 s)                 |

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.