

ATV650U55N4E

Schneider Electric ATV650U55N4E - Altivar Process ATV650 Variable Speed Drive 5.5kW/7.5HP 380-480V IP55 with disconnect switch

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	ATV650U55N4E
PRODUCT FAMILY	CATEGORY
Altivar Process ATV600	VFD
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

This Altivar Process ATV600 variable speed drive can feed 3-phase synchronous and asynchronous power motors. It features 3 built-in RJ45 communication ports as standard, 1 Ethernet port, 2 serial ports. It works at a rated supply voltage from 380V to 480V AC. This drive provides up to 30% energy saving when on standby due to the innovative ??Stop and Go??operation without additional costs. It is suitable for motors with power rating up to 5.5kW / 7.5hp for applications requiring slight overload (up to 120%). It is suitable for motors with power rating up to 4kW / 5hp for applications requiring significant overload (up to 150%). It weighs 10.7kg and its dimensions are, 264mm wide, 678mm high, 300mm deep. This drive is focused on fluids management processing and energy saving, it offers extensive flexibility in water and wastewater, mining, minerals and metals, oil and gas and food and beverage applications. Accessories (fan kit, graphic display terminal) and options (I/O expansion modules, communication modules, EMC input filters) are available with Altivar Process ATV600 drives, depending on the drive rating. It is designed to be mounted in vertical position (+/- 10 °) on a wall. This new concept of drives meets the major needs of process and utilities in terms of equipment efficiency and total cost of ownership by supporting the energy management, asset management and also the overall performance of the process. Schneider Electric ATV650U55N4E is the exact manufacturer refer

RECORDED SPECIFICATIONS

Depth	300 mm
Width	264 mm
Height	678 mm
Phases	3 phases
Weight	10.7 kg
EMC filter	Integrated (C3 <= 150 m, C2 <= 50 m)
IP protection	IP55
Supply voltage	380...480 V
Safety function	STO (SIL 3)
Output frequency range	0.1...599 Hz

ADDITIONAL SPECIFICATIONS

Manufacturer part number	ATV650U55N4E
Rated power (Heavy duty)	4 kW / 5 hp
Rated power (Normal duty)	5.5 kW / 7.5 hp
Nominal switching frequency	4 kHz
Continuous output current (Heavy duty)	9.3 A
Continuous output current (Normal duty)	12.7 A

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.