ATV650U75N4E

Schneider Electric ATV650U75N4E - variable speed drive ATV650 - 7.5kW/10HP - 380...480V - IP55 - disconnect switch

BRAND
Schneider Electric

PRODUCT FAMILY
Altivar Process ATV600

SUPPLY BASIS
RFQ / on request - no stock claim

ORDER CODE / PRODUCT REFERENCE
ATV650U75N4E

CATEGORY
VFD

RECORD IDENTITY
Catalog identity matched

PRODUCT DESCRIPTION

This Altivar Process ATV600 variable speed drive can feed 3-phase synchronous and asynchronous power motors. It features 3 built-in RJ45 communication ports as standard, 1 Ethernet port, 2 serial ports. It works at a rated supply voltage from 380V to 480V AC. This drive provides up to 30% energy saving when on standby due to the innovative ??Stop and Go??operation without additional costs. It is suitable for motors with power rating up to 7.5kW / 10hp for applications requiring slight overload (up to 120%). It is suitable for motors with power rating up to 5.5kW / 7.5hp for applications requiring significant overload (up to 150%). It weighs 13.7kg and its dimensions are, 264mm wide, 678mm high, 330mm deep. This drive is focused on fluids management processing and energy saving, it offers extensive flexibility in water and wastewater, mining, minerals and metals, oil and gas and food and beverage applications. Accessories (fan kit, graphic display terminal) and options (I/O expansion modules, communication modules, EMC input filters) are available with Altivar Process ATV600 drives, depending on the drive rating. It is designed to be mounted in vertical position (+/- 10 °) on a wall. This new concept of drives meets the major needs of process and utilities in terms of equipment efficiency and total cost of ownership by supporting the energy management, asset management and also the overall performance of the process. Schneider Electric ATV650U75N4E is the exact manufacturer re

RECORDED SPECIFICATIONS

Depth	330 mm
Width	264 mm
Height	678 mm
Weight	13.7 kg
IP rating	IP55
Number of phases	3 phases
Output frequency	0.1...599 Hz
Supply frequency	50...60 Hz
Rated supply voltage	380...480 V
Manufacturer part number	ATV650U75N4E

ADDITIONAL SPECIFICATIONS

Motor power (Heavy Duty)	5.5 kW
Motor power (Normal Duty)	7.5 kW
Motor power HP (Heavy Duty)	7.5 hp
Nominal switching frequency	4 kHz
Motor power HP (Normal Duty)	10 hp
Continuous output current (Heavy Duty)	12.7 A
Continuous output current (Normal Duty)	16.5 A

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.