

ATV930D11Y6

Schneider Electric ATV930D11Y6 - Altivar Process ATV930 Variable Speed Drive 11kW 500-690V IP00

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	ATV930D11Y6
PRODUCT FAMILY	CATEGORY
Altivar Process ATV900	Variable Frequency Drive
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

This Altivar Process ATV900 variable speed drive can feed 3-phase synchronous and asynchronous power motors. It is suitable for motors with power rating up to 11kW/15HP for applications requiring slight overload (up to 120%). Schneider Electric ATV930D11Y6 is the exact manufacturer reference for Altivar Process ATV930 Variable Speed Drive 11kW 500-690V IP00 in the Altivar Process ATV900 family. Recorded technical characteristics include Motor Power: 11 kW / 15 hp; Network Phases: 3 phases; Network Frequency: 50...60 Hz; Relay Output Number: 3; Degree of Protection: IP00; Prospective Line Isc: 70 kA; Rated Supply Voltage: 500...690 V; Analogue Input Number: 3. For an RFQ, use the complete part number ATV930D11Y6 so the required rating, configuration and compatible accessories remain exact. Review the linked manufacturer data sheet against the supply system, load, enclosure, environmental conditions and applicable standards before final engineering selection. This listing is intended for project, maintenance and replacement enquiries across Egypt, GCC and the wider MENA region; it does not claim local stock.

RECORDED SPECIFICATIONS

Motor Power	11 kW / 15 hp
Network Phases	3 phases
Network Frequency	50...60 Hz
Relay Output Number	3
Degree of Protection	IP00
Prospective Line Isc	70 kA
Rated Supply Voltage	500...690 V
Analogue Input Number	3
Discrete Input Number	10
Analogue Output Number	2

ADDITIONAL SPECIFICATIONS

Communication Protocols	Modbus TCP, EtherNet/IP, Modbus serial
Manufacturer part number	ATV930D11Y6
Maximum Output Frequency	599 Hz
Motor Power (Heavy Duty)	5.5 kW
Line Current (Heavy Duty)	10.4 A at 500 V, 10.5 A at 690 V
Motor Power (Normal Duty)	7.5 kW
Line Current (Normal Duty)	13.6 A at 500 V, 14.7 A at 690 V
Apparent Power (Heavy Duty)	12.5 kVA at 690 V
Nominal Switching Frequency	4 kHz
Apparent Power (Normal Duty)	17.6 kVA at 690 V
Continuous Output Current (Heavy Duty)	9.5 A at 4 kHz
Maximum Transient Current (Heavy Duty)	14.3 A during 60 s
Continuous Output Current (Normal Duty)	13.5 A at 4 kHz
Maximum Transient Current (Normal Duty)	16.2 A during 60 s

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.