

C114050LS

Schneider Electric C114050LS - Switch disconnecter, ComPacT NSXm 50NA, 4 poles, thermal current Ith 50A, EverLink lugs

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	C114050LS
PRODUCT FAMILY	CATEGORY
ComPacT NSXm	Switch disconnecter
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

Schneider Electric C114050LS is the exact active commercial reference for Switch disconnecter, ComPacT NSXm 50NA, 4 poles, thermal current Ith 50A, EverLink lugs in the ComPacT NSXm range. This low-voltage molded-case circuit breaker or switch-disconnector is used for protection, isolation and distribution in industrial control panels, MCCs, commercial buildings, infrastructure, water systems, HVAC equipment and OEM machinery. Official Schneider characteristics include Range: ComPacT; Product name: ComPacT NSXm; Device short name: NSXm 50NA; Product or component type: Switch disconnecter; Device application: Distribution; Poles description: 4P; [Ith] conventional free air thermal current: 50 A at 40 °C; [Ie] rated operational current: AC-23: 50 A AC 50/60 Hz AC-22: 50 A AC 50/60 Hz. ComPacT NSXm devices provide compact circuit-protection and switching solutions for panel builders and electrical-system integrators. The reference appears in Schneider Electric catalog LVPED221001EN version 4.0 and its exact regional product page confirms current commercial availability. Use the complete part number C114050LS for an RFQ so pole count, trip unit, rated current, breaking capacity and terminal configuration remain exact. Review the linked official Schneider product data sheet against the network voltage, fault level, coordination study, installation conditions and applicable standards before final engineering selection.

RECORDED SPECIFICATIONS

Range	ComPacT
Network type	AC
Product name	ComPacT NSXm
Visible break	No
mounting mode	Fixed
Device short name	NSXm 50NA
Poles description	4P
Device application	Distribution
Official lifecycle	Current official manufacturer lifecycle evidence
Utilisation category	AC-22A AC-23A

ADDITIONAL SPECIFICATIONS

Breaking capacity code	NA
Manufacturer part number	C114050LS
Product or component type	Switch disconnecter
Suitability for isolation	Yes conforming to EN/IEC 60947-3
Contact position indicator	Yes
[Ie] rated operational current	AC-23: 50 A AC 50/60 Hz AC-22: 50 A AC 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Ith] conventional free air thermal current	50 A at 40 °C

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.