# C11B34V100B

## Schneider Electric C11B34V100B - ComPacT NSXmB - disj Vigi - MicroLogic 4.1 100A - 3P3D - 25kA - borne à cosses

**BRAND**
Schneider Electric

**PRODUCT FAMILY**
ComPacT NSXm

**SUPPLY BASIS**
RFQ / on request - no stock claim

**ORDER CODE / PRODUCT REFERENCE**
C11B34V100B

**CATEGORY**
Molded case circuit breaker

**RECORD IDENTITY**
Catalog identity matched

### PRODUCT DESCRIPTION

Schneider Electric C11B34V100B is the exact active commercial reference for ComPacT NSXmB - disj Vigi - MicroLogic 4.1 100A - 3P3D - 25kA - borne à cosses in the ComPacT NSXm range. This low-voltage molded-case circuit breaker or switch-disconnector is used for protection, isolation and distribution in industrial control panels, MCCs, commercial buildings, infrastructure, water systems, HVAC equipment and OEM machinery. Official Schneider characteristics include Gamme: ComPacT; Nom du produit: ComPacT NSXm; Nom de l'appareil: NSXm 160B; Type de produit ou équipement: Disjoncteur différentiel; Application de l'appareil: Distribution; Description des pôles: 3P; Description des pôles protégés: 3D; [In] courant nominal: 100 A à 40 °C. ComPacT NSXm devices provide compact circuit-protection and switching solutions for panel builders and electrical-system integrators. The reference appears in Schneider Electric catalog LVPED221001EN version 4.0 and its exact regional product page confirms current commercial availability. Use the complete part number C11B34V100B for an RFQ so pole count, trip unit, rated current, breaking capacity and terminal configuration remain exact. Review the linked official Schneider product data sheet against the network voltage, fault level, coordination study, installation conditions and applicable standards before final engineering selection.

### RECORDED SPECIFICATIONS

| | |
|---|---|
| **Gamme** | ComPacT |
| **Nom du produit** | ComPacT NSXm |
| **Type de réseau** | CA |
| **Nom de l'appareil** | NSXm 160B |
| **Official lifecycle** | Current official manufacturer lifecycle evidence |
| **Catégorie d'emploi** | Catégorie A |
| **Nom du déclencheur** | MicroLogic 4.1 |
| **[In] courant nominal** | 100 A à 40 °C |
| **Fréquence du réseau** | 50/60 Hz |
| **Niveau de performance** | B 25 kA 415 V CA |

## ADDITIONAL SPECIFICATIONS

| | |
|---|---|
| **Description des pôles** | 3P |
| **Manufacturer part number** | C11B34V100B |
| **Application de l'appareil** | Distribution |
| **Aptitude au sectionnement** | Oui se conformer à CEI 60947-2 |
| **Type de produit ou équipement** | Disjoncteur différentiel |
| **[Ue] tension assignée d'emploi** | 440 V CA 50/60 Hz |
| **Description des pôles protégés** | 3D |

## MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.