

C1035Z100

Schneider Electric C1035Z100 - Trip unit MicroLogic 5.2AZ, ComPacT NSX100/160/250, 3 poles, electronic basic protections, special applications, 100A

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	C1035Z100
PRODUCT FAMILY	CATEGORY
ComPacT NSX	Trip unit
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

Schneider Electric C1035Z100 is the exact active commercial reference for Trip unit MicroLogic 5.2AZ, ComPacT NSX100/160/250, 3 poles, electronic basic protections, special applications, 100A in the ComPacT NSX range. This molded-case circuit breaker is used for protection, isolation and distribution in industrial panels, MCCs, OEM machinery, buildings, water, HVAC and infrastructure. Official Schneider characteristics include Range: ComPacT; Range of product: ComPacT NSX100...250; Product or component type: Trip unit; Trip unit name: MicroLogic 5.2 A-Z; Trip unit technology: Electronic; Range compatibility: ComPacT NSX100 ComPacT NSX160 ComPacT NSX250; Device application: 16 Hz 2/3 networks; Poles description: 3P. The exact regional product page confirms current availability. Use complete part number C1035Z100 for an RFQ so poles, trip unit, rated current, breaking capacity and terminals remain exact. Review the official data sheet against fault level, coordination study, installation conditions and applicable standards before engineering selection.

RECORDED SPECIFICATIONS

Range	ComPacT
Trip unit name	MicroLogic 5.2 A-Z
Protection type	
Range of product	ComPacT NSX100...250
Trip unit rating	100 A at 40 °C
Poles description	3P
Device application	16 Hz 2/3 networks
Official lifecycle	Current official manufacturer lifecycle evidence
Range compatibility	ComPacT NSX100 ComPacT NSX160 ComPacT NSX250
Trip unit technology	Electronic

ADDITIONAL SPECIFICATIONS

Manufacturer part number	C1035Z100
Product or component type	Trip unit
Protected poles description	3D
Circuit breaker mounting mode	Fixed
Trip unit protection functions	LSI
[Ue] rated operational voltage	250/500 V AC 16 Hz 2/3
	40...100 A
	Adjustable 9 settings

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.