

C163MG125D

Schneider Electric C163MG125D - ComPacT NSX - Déclencheur magnéto-thermique TM-DC-G 125A - 3P3D pour NSX160DC

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	C163MG125D
PRODUCT FAMILY	CATEGORY
ComPacT NSX	Control and signaling unit
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

Schneider Electric C163MG125D is the exact active commercial reference for ComPacT NSX - Déclencheur magnéto-thermique TM-DC-G 125A - 3P3D pour NSX160DC in the ComPacT NSX range. This molded-case circuit breaker is used for protection, isolation and distribution in industrial panels, MCCs, OEM machinery, buildings, water, HVAC and infrastructure. Official Schneider characteristics include Gamme: ComPacT; Gamme de produit: ComPacT NSX100...250 DC; Type de produit ou équipement: Déclencheur; Nom du déclencheur: TM-G; Technologie du déclencheur: Thermique-magnétique; Compatibilité de gamme: ComPacT NSX100 DC ComPacT NSX160 DC ComPacT NSX250 DC; Application de l'appareil: Générateur; Description des pôles: 3P. The exact regional product page confirms current availability. Use complete part number C163MG125D for an RFQ so poles, trip unit, rated current, breaking capacity and terminals remain exact. Review the official data sheet against fault level, coordination study, installation conditions and applicable standards before engineering selection.

RECORDED SPECIFICATIONS

Gamme	ComPacT
Type de réseau	CC
Gamme de produit	ComPacT NSX100...250 DC
Official lifecycle	Current official manufacturer lifecycle evidence
Type de protection	L : for protection surcharge (thermique) I : for protection (magnétique) court-circuit
Nom du déclencheur	TM-G
Description des pôles	3P
Calibre du déclencheur	125 A à 40 °C
Compatibilité de gamme	ComPacT NSX100 DC ComPacT NSX160 DC ComPacT NSX250 DC
Manufacturer part number	C163MG125D

ADDITIONAL SPECIFICATIONS

Application de l'appareil	Générateur
Technologie du déclencheur	Thermique-magnétique
Type de produit ou équipement	Déclencheur
[Ue] tension assignée d'emploi	750 V CC
Description des pôles protégés	3D
Mode d'installation du disjoncteur	Fixe
Fonctions de protection du déclencheur	LI
	Réglable

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.