LC1D09ND

Schneider Electric LC1D09ND - Contactor, TeSys Deca, 3P(3NO), AC-3/3e, <=440V, 9A, 60V DC coil, screw clamp terminals

BRAND
Schneider Electric

PRODUCT FAMILY
TeSys Deca

SUPPLY BASIS
RFQ / on request - no stock claim

ORDER CODE / PRODUCT REFERENCE
LC1D09ND

CATEGORY
Contactor

RECORD IDENTITY
Catalog identity matched

PRODUCT DESCRIPTION

TeSys D contactor, 3 poles (3NO), for motor control applications up to 9A/690V AC-3/3e (4kW@400V). It provides a 60V DC coil, 1NO+1NC built-in auxiliary contacts (NC mirror certified), connection by screw clamp terminals. For operating rates until 3600 cycles/hour and environments until 60°C, it procures high reliability and durability to demanding applications. Compact (45mm width), DIN-rail mounting or screw fixing. Multi standards certified (IEC, UL, CSA, CCC, EAC, Marine), Green Premium compliant (RoHS/REACh). Schneider Electric LC1D09ND is the exact active commercial reference for Contactor, TeSys Deca, 3P(3NO), AC-3/3e, <=440V, 9A, 60V DC coil, screw clamp terminals in the TeSys Deca range for industrial motor and load control. This contactor supports industrial motor starters, process equipment, pumps, compressors, HVAC installations and heavy-duty electrical panels. Official Schneider characteristics include Range of product: TeSys Deca; Product or component type: Contactor; Device short name: LC1D; Contactor application: Motor control Resistive load; Utilisation category: AC-4 AC-3 AC-1 AC-3e; Poles description: 3P; [Ue] rated operational voltage: Power circuit: Power circuit: <= 300 V DC; [Ie] rated operational current: 9 A (at 25 A (at 9 A (at <60 °C) at <= 440 V AC AC-3e for power circuit. The reference appears in Schneider Electric TeSys catalog MKTED210011EN version 17.1 and its exact regional product page confirms current commercial availability. For an RFQ, us

RECORDED SPECIFICATIONS

Motor power hp	
Motor power kW	
Protective cover	With
Range of product	TeSys Deca
Device short name	LC1D
Poles description	3P
Compatibility code	LC1D
Official lifecycle	Current official manufacturer lifecycle evidence
Utilisation category	AC-4 AC-3 AC-1 AC-3e
Contactor application	Motor control Resistive load

ADDITIONAL SPECIFICATIONS

Manufacturer part number	LC1D09ND
Pole contact composition	3 NO
Product or component type	Contactor
Irms rated making capacity	
[Uc] control circuit voltage	60 V DC
[Ie] rated operational current	9 A (at 25 A (at 9 A (at <60 °C) at <= 440 V AC AC-3e for power circuit
[Ue] rated operational voltage	Power circuit: Power circuit: <= 300 V DC
[Ith] conventional free air thermal current	25 A (at 60 °C) for power circuit 10 A (at 60 °C) for signalling circuit

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.