LC1D126BL

Schneider Electric LC1D126BL - Contactor, TeSys Deca, 3P(3NO), AC-3/AC-3e, <=440V, 12A, 24V DC low consumption coil, lugs-ring terminals

BRAND
Schneider Electric

PRODUCT FAMILY
TeSys Deca

SUPPLY BASIS
RFQ / on request - no stock claim

ORDER CODE / PRODUCT REFERENCE
LC1D126BL

CATEGORY
Contactor

RECORD IDENTITY
Catalog identity matched

PRODUCT DESCRIPTION

TeSys D contactor, 3 poles (3NO), for motor control applications up to 12A/690V AC-3/3e (5.5kW@400V). It provides a low consumption 24V DC coil with transient suppressor module, 1NO+1NC built-in auxiliary contacts (NC mirror certified), connection by ring-lugs screw terminals. For operating rates until 3600 cycles/hour and environments until 60°C, it procures high reliability and durability. Compact (45mm width), DIN-rail mounting or screw fixing. Multi standards certified (IEC, UL, CSA, CCC, EAC, Marine), Green Premium compliant (RoHS/REACh). Schneider Electric LC1D126BL is the exact active commercial reference for Contactor, TeSys Deca, 3P(3NO), AC-3/AC-3e, <=440V, 12A, 24V DC low consumption coil, lugs-ring terminals in the TeSys Deca range for industrial motor and load control. This contactor supports industrial motor starters, process equipment, pumps, compressors, HVAC installations and heavy-duty electrical panels. Official Schneider characteristics include Range of product: TeSys Deca; Product or component type: Contactor; Device short name: LC1D; Contactor application: Resistive load Motor control; Utilisation category: AC-4 AC-1 AC-3 AC-3e; Poles description: 3P; [Ue] rated operational voltage: Power circuit: Power circuit: <= 300 V DC; [Ie] rated operational current: 25 A (at 12 A (at 12 A (at <60 °C) at <= 440 V AC AC-3e for power circuit. The reference appears in Schneider Electric TeSys catalog MKTED210011EN version 17.1 and its exact regional product page confi

RECORDED SPECIFICATIONS

Motor power hp	
Motor power kW	
Protective cover	With
Range of product	TeSys Deca
Device short name	LC1D
Poles description	3P
Compatibility code	LC1D
Official lifecycle	Current official manufacturer lifecycle evidence
Utilisation category	AC-4 AC-1 AC-3 AC-3e
Contactor application	Resistive load Motor control

ADDITIONAL SPECIFICATIONS

Manufacturer part number	LC1D126BL
Pole contact composition	3 NO
Product or component type	Contactor
Irms rated making capacity	
[Uc] control circuit voltage	24 V DC
[Ie] rated operational current	25 A (at 12 A (at 12 A (at <60 °C) at <= 440 V AC AC-3e for power circuit
[Ue] rated operational voltage	Power circuit: Power circuit: <= 300 V DC
[Ith] conventional free air thermal current	25 A (at 60 °C) for power circuit 10 A (at 60 °C) for signalling circuit

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.