LC1D40008U7

Schneider Electric LC1D40008U7 - Contactor, TeSys Deca, 4P(2NO+2NC),AC-1 , <=440V, 60 A 240V AC 50/60Hz coil, screw clamp terminal

BRAND
Schneider Electric

PRODUCT FAMILY
TeSys Deca

SUPPLY BASIS
RFQ / on request - no stock claim

ORDER CODE / PRODUCT REFERENCE
LC1D40008U7

CATEGORY
Contactor

RECORD IDENTITY
Catalog identity matched

PRODUCT DESCRIPTION

TeSys Deca contactor, 4 poles (2NO/2NC),for load control applications in category AC-1. and for non-inductive load control applications up to 60A@60?. It provides a 240V 50/60Hz standard AC coil,without built-in auxiliary contact, connection by screw clamp terminals. For operating rates until 3600 cycles/hour and environments until 60°C, it procures reliability and durability to standard applications. Very compact (55mm width), DIN-rail mounting or screw fixing. Multi standards certified (IEC, UL, CSA, CCC, EN), Green Premium compliant (RoHS/REACh). Schneider Electric LC1D40008U7 is the exact active commercial reference for Contactor, TeSys Deca, 4P(2NO+2NC),AC-1 , <=440V, 60 A 240V AC 50/60Hz coil, screw clamp terminal in the TeSys Deca range for industrial motor and load control. This contactor supports industrial motor starters, process equipment, pumps, compressors, HVAC installations and heavy-duty electrical panels. Official Schneider characteristics include Range: TeSys; Range of product: TeSys Deca; Product or component type: Contactor; Device short name: LC1D; Contactor application: Resistive load; Utilisation category: AC-1; Poles description: 4P; [Ue] rated operational voltage: Power circuit: <= 1000 V AC 25...400 Hz. The reference appears in Schneider Electric TeSys catalog MKTED210011EN version 17.1 and its exact regional product page confirms current commercial availability. For an RFQ, use the complete part number LC1D40008U7 so the rated current, pole configur

RECORDED SPECIFICATIONS

Range	TeSys
Protective cover	Without
Range of product	TeSys Deca
Device short name	LC1D
Poles description	4P
Compatibility code	LC1D
Official lifecycle	Current official manufacturer lifecycle evidence
Utilisation category	AC-1
Contactor application	Resistive load
Rated breaking capacity	800 A at 440 V for power circuit conforming to IEC 60947

ADDITIONAL SPECIFICATIONS

Manufacturer part number	LC1D40008U7
Pole contact composition	2 NO + 2 NC
Product or component type	Contactor
Irms rated making capacity	800 A at 440 V for power circuit conforming to IEC 60947
[Uc] control circuit voltage	240 V AC 50/60 Hz
[Ie] rated operational current	60 A (at <60 °C) at <= 440 V AC AC-1 for power circuit
[Ue] rated operational voltage	Power circuit: <= 1000 V AC 25...400 Hz
[Ith] conventional free air thermal current	60 A (at 60 °C) for power circuit

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.