

LC1D806LE7

TeSys Deca;contactor;LC1D806LE7

|                                   |                                |
|-----------------------------------|--------------------------------|
| BRAND                             | ORDER CODE / PRODUCT REFERENCE |
| Schneider Electric                | LC1D806LE7                     |
| PRODUCT FAMILY                    | CATEGORY                       |
| TeSys Deca                        | Contactor                      |
| SUPPLY BASIS                      | RECORD IDENTITY                |
| RFQ / on request - no stock claim | Catalog identity matched       |

PRODUCT DESCRIPTION

RECORDED SPECIFICATIONS

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Range                | TeSys                                            |
| Motor power hp       |                                                  |
| Motor power kW       |                                                  |
| Protective cover     | With                                             |
| Range of product     | TeSys Deca                                       |
| Device short name    | LC1D                                             |
| Poles description    | 3P                                               |
| Compatibility code   | LC1D                                             |
| Official lifecycle   | Current official manufacturer lifecycle evidence |
| Utilisation category | AC-3 AC-3e AC-4 AC-1                             |

ADDITIONAL SPECIFICATIONS

|                                             |                                                                            |
|---------------------------------------------|----------------------------------------------------------------------------|
| Contactor application                       | Motor control Resistive load                                               |
| Manufacturer part number                    | LC1D806LE7                                                                 |
| Pole contact composition                    | 3 NO                                                                       |
| Product or component type                   | Contactor                                                                  |
| [Uc] control circuit voltage                | 208 V AC 50/60 Hz                                                          |
| [Ie] rated operational current              | 125 A (at 80 A (at 80 A (at <60 °C) at <= 440 V AC AC-3e for power circuit |
| [Ue] rated operational voltage              | Power circuit: Power circuit: <= 690 V AC                                  |
| [Ith] conventional free air thermal current | 10 A (at 60 °C) for signalling circuit 125 A (at 60 °C) for power circuit  |

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.