LC1DT80A6BNE

Schneider Electric LC1DT80A6BNE - Contactor, TeSys Deca Advanced, 4P(4NO), AC-1, <=440V, 80A, 24...60V AC/DC coil, lugs-ring terminals

BRAND
Schneider Electric

PRODUCT FAMILY
TeSys Deca

SUPPLY BASIS
RFQ / on request - no stock claim

ORDER CODE / PRODUCT REFERENCE
LC1DT80A6BNE

CATEGORY
Contactor

RECORD IDENTITY
Catalog identity matched

PRODUCT DESCRIPTION

TeSys D contactor, 4 poles (4NO), for non-inductive load applications up to 80A/690V AC-1. It provides a low consumption 24-60V AC/DC coil with electronic control, 1NO+1NC built-in auxiliary contacts (NC mirror certified), connection by ring-lugs screw terminals. For operating rates until 3600 cycles/hour and environments until 60°C, it procures high reliability and durability. Compact (70mm width), DIN-rail mounting or screw fixing. Multi standards certified (IEC, UL, CSA, CCC, EAC, Marine), Green Premium compliant (RoHS/REACh). Schneider Electric LC1DT80A6BNE is the exact active commercial reference for Contactor, TeSys Deca Advanced, 4P(4NO), AC-1, <=440V, 80A, 24...60V AC/DC coil, lugs-ring terminals in the TeSys Deca range for industrial motor and load control. This contactor supports industrial motor starters, process equipment, pumps, compressors, HVAC installations and heavy-duty electrical panels. Official Schneider characteristics include Range of product: TeSys Deca Advanced; Product or component type: Contactor; Device short name: LC1D; Contactor application: Resistive load; Utilisation category: AC-1; Poles description: 4P; [Ue] rated operational voltage: Power circuit: <= 690 V AC 25...400 Hz; [Ie] rated operational current: 80 A (at <60 °C) at <= 440 V AC-1 for power circuit. The reference appears in Schneider Electric TeSys catalog MKTED210011EN version 17.1 and its exact regional product page confirms current commercial availability. For an RFQ, use the compl

RECORDED SPECIFICATIONS

Protective cover	With
Range of product	TeSys Deca Advanced
Device short name	LC1D
Poles description	4P
Compatibility code	LC1D
Official lifecycle	Current official manufacturer lifecycle evidence
Utilisation category	AC-1
Contactor application	Resistive load
Rated breaking capacity	1000 A at 440 V for power circuit conforming to IEC 60947
Manufacturer part number	LC1DT80A6BNE

ADDITIONAL SPECIFICATIONS

Pole contact composition	4 NO
Product or component type	Contactor
Irms rated making capacity	
[Uc] control circuit voltage	24...60 V AC 50/60 Hz 24...60 V DC
[Ie] rated operational current	80 A (at <60 °C) at <= 440 V AC-1 for power circuit
[Ue] rated operational voltage	Power circuit: <= 690 V AC 25...400 Hz
[Icw] rated short-time withstand current	
[Ith] conventional free air thermal current	80 A (at 60 °C) for power circuit 10 A (at 60 °C) for signalling circuit

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.