# GV2LE22

| | |
|---|---|
| **BRAND**<br>Schneider Electric | **ORDER CODE / PRODUCT REFERENCE**<br>GV2LE22 |
| **PRODUCT FAMILY**<br>TeSys Deca GV2LE | **CATEGORY**<br>Motor circuit breaker |
| **SUPPLY BASIS**<br>RFQ / on request - no stock claim | **RECORD IDENTITY**<br>Catalog identity matched |

## PRODUCT DESCRIPTION

Start-stop control by toggle guaranteed for 100 000 cycles AC-3. To complete motor protection, use in association with a thermal overload relay LRD22 (to be ordered separately). Multi standards certified (IEC, UL, CSA, CCC, EAC, Marine). Multi standards certified (IEC, UL, CSA, CCC, EAC, Marine), Green Premium compliant (RoHS/REACh). Schneider Electric GV2LE22 is the exact active commercial reference for GV2LE;TeSys GV;motor circuit breaker;motor protection;magnetic protection;high breaking capacity;toggle;screw clamp terminals, a TeSys Deca Frame 2 magnetic motor circuit breaker with toggle control and screw clamp terminals. Official Schneider characteristics include Range: TeSys Deca; Product name: TeSys GV2; Product or component type: Motor circuit breaker; Device short name: GV2LE; Device application: Motor protection; Trip unit technology: Magnetic; Poles description: 3P; Network type: AC. The reference is documented in Schneider Electric TeSys catalog MKTED210011EN version 17.1 on B6/13. TeSys motor-protection devices are used in industrial motor starters and panels serving pumps, water systems, HVAC equipment, conveyors, compressors and OEM machinery. For an RFQ, use the complete part number GV2LE22 so the current range, trip technology, control mechanism, terminal arrangement and coordination requirements remain exact. Review the linked official Schneider data sheet against the motor full-load current, starting profile, prospective fault current, supply voltage, coord

## RECORDED SPECIFICATIONS

| | |
|---|---|
| **Range** | TeSys Deca |
| **Control type** | Toggle |
| **Network type** | AC |
| **Product name** | TeSys GV2 |
| **Motor power kW** | |
| **Breaking capacity** | |
| **Device short name** | GV2LE |
| **Network frequency** | 50/60 Hz conforming to IEC 60947-2 |
| **Poles description** | 3P |
| **Device application** | Motor protection |

## ADDITIONAL SPECIFICATIONS

| | |
|---|---|
| **Official lifecycle** | Current official manufacturer lifecycle evidence |
| **[In] rated current** | 25 A |
| **Trip unit technology** | Magnetic |
| **Utilisation category** | |
| **Manufacturer part number** | GV2LE22 |
| **Magnetic tripping current** | 388.3 A |
| **Product or component type** | Motor circuit breaker |

## MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.