# GV3L65

**BRAND**
Schneider Electric

**PRODUCT FAMILY**
TeSys Deca GV3L

**SUPPLY BASIS**
RFQ / on request - no stock claim

**ORDER CODE / PRODUCT REFERENCE**
GV3L65

**CATEGORY**
Motor circuit breaker

**RECORD IDENTITY**
Catalog identity matched

## PRODUCT DESCRIPTION

Start-stop control by rotary handle guaranteed for 50 000 cycles AC-3. To complete motor protection, use it in association with a thermal overload relay LRD365 (to be ordered separately). Multi standards certified (IEC, CCC, EAC, Marine). Multi standards certified (IEC, CCC, EAC, Marine), Green Premium compliant (RoHS/REACh). Schneider Electric GV3L65 is the exact active commercial reference for GV3L;TeSys GV;motor circuit breaker;motor protection;magnetic protection;high breaking capacity;rotary handle;EverLink terminals, a TeSys Deca Frame 3 magnetic motor circuit breaker with rotary handle control and EverLink BTR screw connectors. Official Schneider characteristics include Range: TeSys Deca; Product name: TeSys GV3; Product or component type: Motor circuit breaker; Device short name: GV3L; Device application: Motor protection; Trip unit technology: Magnetic; Poles description: 3P; Network type: AC. The reference is documented in Schneider Electric TeSys catalog MKTED210011EN version 17.1 on B6/26. TeSys motor-protection devices are used in industrial motor starters and panels serving pumps, water systems, HVAC equipment, conveyors, compressors and OEM machinery. For an RFQ, use the complete part number GV3L65 so the current range, trip technology, control mechanism, terminal arrangement and coordination requirements remain exact. Review the linked official Schneider data sheet against the motor full-load current, starting profile, prospective fault current, supply voltage

## RECORDED SPECIFICATIONS

| | |
|---|---|
| **Range** | TeSys Deca |
| **Control type** | Rotary handle |
| **Network type** | AC |
| **Product name** | TeSys GV3 |
| **Motor power kW** | 30 kW at 400/415 V AC 50/60 Hz 37 kW at 500 V AC 50/60 Hz 55 kW at 690 V AC 50/60 Hz |
| **Breaking capacity** | |
| **Device short name** | GV3L |
| **Network frequency** | 50/60 Hz conforming to IEC 60947-2 |
| **Poles description** | 3P |
| **Device application** | Motor protection |

## ADDITIONAL SPECIFICATIONS

| | |
|---|---|
| **Official lifecycle** | Current official manufacturer lifecycle evidence |
| **[In] rated current** | 65 A |
| **Trip unit technology** | Magnetic |
| **Utilisation category** | Category A conforming to IEC 60947-2 AC-3 conforming to IEC 60947-4-1 |
| **Manufacturer part number** | GV3L65 |
| **Magnetic tripping current** | 910 A |
| **Product or component type** | Motor circuit breaker |

## MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.