

C125N350FM

Schneider Electric C125N350FM - Circuit breaker, ComPacT NS1250N

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	C125N350FM
PRODUCT FAMILY	CATEGORY
ComPacT NS new generation	Circuit Breaker
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

ComPacT NS is designed to optimize space and breaking capacity, it is an optimal choice for all standard and specific applications. The operational current is 1250A. The operational voltage is 690VAC 50/60Hz. The breaking capacity (Icu) is 50kA rms at 415VAC 50/60Hz. The circuit breaker can be manually operated with its toggle. The electronic MicroLogic 5.0 control unit has a 1250A rating. MicroLogic 5.0 control unit provides an overload protection (true rms and adjustable long time protection). MicroLogic 5.0 control unit provides adjustable short-circuit protections (rms short time and instantaneous protections). MicroLogic 5.0 control unit provides adjustable long time, short time and instantaneous protections (ANSI codes 49/51/50). The circuit breaker can be manually operated with ON, OFF or "push to trip" buttons. The circuit breaker is equipped with front connections terminals at top and bottom sides. This product comes with a variety of optional functions and accessories. The dimensions (without the toggle) are 327mm (Heigh) x 210mm (Width) x 147mm (Depth). It is compliant with IEC 60947-1 and IEC60947-2 international standards. ComPacT NS can be integrated within Schneider Electric EcoStruxure Power architecture. ComPacT NS is part of the global Schneider Electric Environmental Program. ComPacT NS new generation is part of Schneider Electric EcoStruxure Power architecture. ComPacT NS new generation is more sustainable with green packaging and green partnerships. This

RECORDED SPECIFICATIONS

Poles	3P
Mounting mode	Fixed
Rated current	1250 A
Product weight	14 kg
Protection functions	LSI
Trip unit technology	Electronic
Dimensions (W x H x D)	210 x 327 x 147 mm
Manufacturer part number	C125N350FM
Rated operational voltage	690 V AC
	50 kA at 380/415 V AC

ADDITIONAL SPECIFICATIONS**MANUFACTURER DOCUMENTATION**

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.