

C40F32D250

Schneider Electric C40F32D250 - ComPacT NSX400F Circuit Breaker with MicroLogic 2.3 Trip Unit 250A

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	C40F32D250
PRODUCT FAMILY	CATEGORY
ComPacT NSX new generation	Circuit Breaker
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

The operational voltage is 690VAC 50/60Hz. This product embeds an electronic MicroLogic 2.3 trip unit, with 250A rating. MicroLogic 2.3 trip unit provides adjustable long time and short time protections, and a fixed instantaneous protection. This 3 poles version (140mm x 255mm x 110mm) comes with a variety of optional functions and accessories. It is compliant with international standards (IEC 60947), CCC, EAC and marine specifications. ComPacT NSX400F is part of Schneider Electric EcoStruxure Power architecture. Schneider Electric C40F32D250 is the exact manufacturer reference for ComPacT NSX400F Circuit Breaker with MicroLogic 2.3 Trip Unit 250A in the ComPacT NSX new generation family. Recorded technical characteristics include Depth: 110 mm; Poles: 3; Width: 140 mm; Height: 255 mm; Standard: EN/IEC 60947-2; Trip unit: MicroLogic 2.3; Net weight: 6.05 kg; Rated current: 250 A. For an RFQ, use the complete part number C40F32D250 so the required rating, configuration and compatible accessories remain exact. Review the linked manufacturer data sheet against the supply system, load, enclosure, environmental conditions and applicable standards before final engineering selection. This listing is intended for project, maintenance and replacement enquiries across Egypt, GCC and the wider MENA region; it does not claim local stock.

RECORDED SPECIFICATIONS

Depth	110 mm
Poles	3
Width	140 mm
Height	255 mm
Standard	EN/IEC 60947-2
Trip unit	MicroLogic 2.3
Net weight	6.05 kg
Rated current	250 A
Trip unit technology	Electronic
Electrical durability	6000 cycles at 440 V In

ADDITIONAL SPECIFICATIONS

Mechanical durability	15000 cycles
Manufacturer order code	C40F32D250
Manufacturer part number	C40F32D250
Rated insulation voltage	800 V AC
Rated operational voltage	690 V AC
Trip unit protection functions	LSol
	36 kA at 380/415 V AC

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.