

LV432641

Schneider Electric LV432641 - Standard Motor Mechanism Module MT400/630

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	LV432641
PRODUCT FAMILY	CATEGORY
ComPact	Circuit Breaker Accessory
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

This is a communicating motor mechanism for Compact NSX 100/160 and PowerPact Multistandard H frame devices that allows automatic device spring-charging. It helps the circuit breaker to feature a high mechanical endurance as well as easy and sure opening or closing operations. It provides a double insulation of the front face and all indications remain visible and accessible. The control voltage of this motor mechanism module is 220VAC to 240VAC 50/60Hz. The consumption is less than 500VA. Padlocking of the device remains possible. Schneider Electric LV432641 is the exact manufacturer reference for Standard Motor Mechanism Module MT400/630 in the ComPact family. Recorded technical characteristics include Control signal type: Impulse, Maintained; Control circuit voltage: 208-277 V AC, 220-240 V AC; Maximum power consumption: 500 VA; Maximum operating frequency: 4 per minute; Circuit breaker frame rated current: 400 A / 630 A; Circuit breaker response time (open): < 700 ms; Circuit breaker response time (closed): < 80 ms. For an RFQ, use the complete part number LV432641 so the required rating, configuration and compatible accessories remain exact. Review the linked manufacturer data sheet against the supply system, load, enclosure, environmental conditions and applicable standards before final engineering selection. This listing is intended for project, maintenance and replacement enquiries across Egypt, GCC and the wider MENA region; it does not claim local stock.

RECORDED SPECIFICATIONS

Control signal type	Impulse, Maintained
Control circuit voltage	208-277 V AC, 220-240 V AC
Manufacturer order code	LV432641
Manufacturer part number	LV432641
Maximum power consumption	500 VA
Maximum operating frequency	4 per minute
Circuit breaker frame rated current	400 A / 630 A
Circuit breaker response time (open)	< 700 ms
Circuit breaker response time (closed)	< 80 ms

ADDITIONAL SPECIFICATIONS**MANUFACTURER DOCUMENTATION**

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.