

RM35TF30

Schneider Electric RM35TF30 - Modular multifunction 3 phase supply control relay, Harmony, 5A, 2CO, 220...480V AC

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	RM35TF30
PRODUCT FAMILY	CATEGORY
Harmony	Industrial Relay
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

This Harmony RM35-T multi function control relay allows monitoring of power supply circuits in 3-phase networks. This modular multi function 3-phase control relay is ideal for monitoring of electrical values in industrial and building control panels. It applies to a wide type of industrial automation applications such as hoisting, packaging, lifts, textile, water. It has one of market medium form-factors with 35mm width, allowing for a flexible and easy installation on DIN rail, using the same space as any modular 3-pole DIN device. It also offers a selectable memory function, integral LED for indicating control status, sealable cover, with simple and precise settings with screw trimmers. It provides automatic shutdown management and fault information to user for a quick fault identification and troubleshooting. Multi function controller for wide choice selected in hard-wired logic automated systems, ideal for refurbishment of old installations without using a PLC. Schneider Electric RM35TF30 is the exact manufacturer reference for Modular multifunction 3 phase supply control relay, Harmony, 5A, 2CO, 220...480V AC in the Harmony family. Recorded technical characteristics include Width: 35 mm; Weight: 0.13 kg; Contacts: 2 C/O; Mounting: 35 mm DIN rail; IP rating: IP30 (casing), IP20 (terminals); Time delay: 0.1-10 s; Rated current: 5 A; Voltage range: 220-480 V AC. For an RFQ, use the complete part number RM35TF30 so the required rating, configuration and compatible accessorie

RECORDED SPECIFICATIONS

Width	35 mm
Weight	0.13 kg
Contacts	2 C/O
Mounting	35 mm DIN rail
IP rating	IP30 (casing), IP20 (terminals)
Time delay	0.1-10 s
Rated current	5 A
Voltage range	220-480 V AC
Operating temperature	-20-50 °C
Manufacturer part number	RM35TF30

ADDITIONAL SPECIFICATIONS

Rated insulation voltage	400 V
--------------------------	-------

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.