

ATS22C25Q

Schneider Electric ATS22C25Q - Altistart 22 Soft Starter for Asynchronous Motors

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	ATS22C25Q
PRODUCT FAMILY	CATEGORY
Altistart 22	Soft Starter
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

This Altistart 22 soft starter can feed 3-phase asynchronous motors in supply line or delta connection. It has a rating of 250A and 230V to 440V, a rated power up to 132kW (400V to 440V in supply line) and up to 220kW (400V to 440V in motor delta connection). It is designed for simple and complex machines such as centrifugal and piston pumps, fans, screw compressors and material handling equipment. Slim form factor improves versatility; allows mounting in frames of any kind of machines. It features an Integrated bypass, this reduces noise and decreases heat dissipation. Compatibility with SoMove software allows configurations and settings to be easily transferred, meaning spares can be quickly installed. It provides smooth starting for your machinery, avoiding mechanical stresses and extending their service life. Schneider Electric ATS22C25Q is the exact manufacturer reference for Altistart 22 Soft Starter for Asynchronous Motors in the Altistart 22 family. Recorded technical characteristics include Depth: 299 mm; Width: 206 mm; Height: 425 mm; Net weight: 33 kg; Motor power: 75 kW (230 V), 132 kW (400-440 V); IP protection: IP00; Assembly style: With heat sink; Number of phases: 3 phases. For an RFQ, use the complete part number ATS22C25Q so the required rating, configuration and compatible accessories remain exact. Review the linked manufacturer data sheet against the supply system, load, enclosure, environmental conditions and applicable standards before final engineering

RECORDED SPECIFICATIONS

Depth	299 mm
Width	206 mm
Height	425 mm
Net weight	33 kg
Motor power	75 kW (230 V), 132 kW (400-440 V)
IP protection	IP00
Assembly style	With heat sink
Number of phases	3 phases
Supply frequency	50...60 Hz
Physical interface	RS485 multidrop

ADDITIONAL SPECIFICATIONS

Rated supply voltage	230...440 V
Starter rating (IcL)	250 A
Utilisation category	AC-53A
Discrete input number	3
Operating temperature	-10?40 °C
Communication protocol	Modbus
Discrete output number	2
Control circuit voltage	230 V
Manufacturer part number	ATS22C25Q

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.