

3RV2011-1EA10

Siemens 3RV2011-1EA10 - SIRIUS 3RV2 Circuit Breaker for Motor Protection S00

|                |                                   |                                |                                  |
|----------------|-----------------------------------|--------------------------------|----------------------------------|
| BRAND          | Siemens                           | ORDER CODE / PRODUCT REFERENCE | 3RV20111EA10                     |
| PRODUCT FAMILY | SIRIUS                            | CATEGORY                       | Motor Protection Circuit Breaker |
| SUPPLY BASIS   | RFQ / on request - no stock claim | RECORD IDENTITY                | Catalog identity matched         |

PRODUCT DESCRIPTION

Circuit breaker size S00 for motor protection, CLASS 10 A-release 2.8...4 A N release 52 A screw terminal Standard switching capacity Siemens 3RV2011-1EA10 is the exact orderable reference for SIRIUS 3RV2 Circuit Breaker for Motor Protection S00 and has been verified as an active product on Siemens Industry Mall. It belongs to SIRIUS 3RV2 motor starter protectors. Recorded manufacturer technical characteristics include Size: S00; Poles: 3; Rated current: 4 A; Terminal type: Screw terminal; Tripping class: CLASS 10; Maximum altitude: 2000 m; Protection class: IP20; N-release current: 52 A. For an RFQ, use the complete part number so the required electrical rating, hardware revision and compatible accessories remain exact. The linked Siemens data sheet should be checked against the application, supply system, environmental conditions and applicable standards before final engineering selection.

RECORDED SPECIFICATIONS

|                  |                                  |
|------------------|----------------------------------|
| Size             | S00                              |
| Poles            | 3                                |
| Trip class       | CLASS 10                         |
| Application      | Motor protection                 |
| Product type     | Motor Protection Circuit Breaker |
| Rated current    | 4 A                              |
| Terminal type    | Screw terminal                   |
| Tripping class   | CLASS 10                         |
| Maximum altitude | 2000 m                           |
| Protection class | IP20                             |

ADDITIONAL SPECIFICATIONS

|                                    |                                                  |
|------------------------------------|--------------------------------------------------|
| N-release current                  | 52 A                                             |
| Official lifecycle                 | Current official manufacturer lifecycle evidence |
| Manufacturer order code            | 3RV20111EA10                                     |
| Adjustable current range           | 2.8...4 A                                        |
| Manufacturer part number           | 3RV2011-1EA10                                    |
| Adjustable A-release range         | 2.8...4 A                                        |
| Ambient operating temperature      | -20 ... +60 °C                                   |
| Insulation voltage rated value     | 690 V                                            |
| Rated operating power (AC-3, 400V) | 1500 W                                           |

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.