

A9D11806

Schneider Electric A9D11806 - Acti9 iC60H RCBO 1P+N 6A C 30mA 240V

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	A9D11806
PRODUCT FAMILY	CATEGORY
Acti9	RCBO
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

This Acti9 iC60 is a modular residual current breaker with overcurrent protection (RCBO). It is a 1P+N circuit breaker with 1 protected pole, 6A In rated current and C tripping curve. The earth leakage protection class is A type with a sensitivity of 30mA. The earth-leakage protection time delay is instantaneous. The Icn rated short circuit breaking capacity is up to 10000A according IEC 61009-2-2 standard. Its unique Visitrip indicator reduces intervention time by showing the faulty circuit. Its Visisafe green strip guarantees the physical opening of the contacts to allow downstream maintenance. Its fast closing mechanism independent of manual operation improves its service life. This product is compliant with IEC 61009-1 and AS/NZS 61009.1 standards. It has an electrical endurance going up to 5000 cycles and a mechanical endurance going up to 20000 cycles. The Ue operational voltage is 240VAC. The Ui rated insulation voltage is 400VAC. The Uimp rated impulse withstand voltage is 4kV. The frequency is 50Hz. It is DIN rail mountable. The width in 9mm pitches is 2. The product color is white (RAL9003). The dimensions are (W) 18mm x (H) 110mm x (D) 77.5mm. The weight is 205g. According to IEC 60529 standard, the degree of protection is IP20 and IP40 in enclosure. The operating temperature is from -15°C to 60°C. The storage temperature is from -40°C to 85°C. Schneider Electric A9D11806 is the exact manufacturer reference for Acti9 iC60H RCBO 1P+N 6A C 30mA 240V in the Acti9 fami

RECORDED SPECIFICATIONS

Poles	1P + N
Rated current	6 A
Tripping curve	C
Breaking capacity Icn	10000 A
IP degree of protection	IP20
Manufacturer part number	A9D11806
Rated insulation voltage	400 V AC
Earth-leakage sensitivity	30 mA
Rated operational voltage	230/240 V AC
Rated impulse withstand voltage	4 kV

ADDITIONAL SPECIFICATIONS**MANUFACTURER DOCUMENTATION**

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.