

ATS22D47Q

Altistart 22 Soft Starter ATS22D47Q for Asynchronous Motors

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	ATS22D47Q
PRODUCT FAMILY	CATEGORY
Altistart 22	Soft Starter
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

This soft starter can feed 3-phase asynchronous motors in supply line or delta connection. It has a rating of 47A and 230V to 440V, a rated power up to 22kW (400V to 440V in supply line) and up to 45kW (400V to 440V in motor delta connection). It is designed for simple and complex machines such as centrifugal and piston pumps, fans, screw compressors and material handling equipment. Slim form factor improves versatility; allows mounting in frames of any kind of machines. It features an Integrated bypass, this reduces noise and decreases heat dissipation. Compatibility with SoMove software allows configurations and settings to be easily transferred, meaning spares can be quickly installed. It provides smooth starting for your machinery, avoiding mechanical stresses and extending their service life. Schneider Electric ATS22D47Q is the exact manufacturer reference for Altistart 22 Soft Starter ATS22D47Q for Asynchronous Motors in the Altistart 22 family. Recorded technical characteristics include Depth: 169 mm; Width: 130 mm; Height: 265 mm; Net weight: 7 kg; Noise level: 45 dB; Starter rating: 47 A; Power dissipation: 48 W; Motor power (230V): 11 kW. For an RFQ, use the complete part number ATS22D47Q so the required rating, configuration and compatible accessories remain exact. Review the linked manufacturer data sheet against the supply system, load, enclosure, environmental conditions and applicable standards before final engineering selection. This listing is intended for pr

RECORDED SPECIFICATIONS

Depth	169 mm
Width	130 mm
Height	265 mm
Net weight	7 kg
Noise level	45 dB
Starter rating	47 A
Power dissipation	48 W
Motor power (230V)	11 kW
Motor power (400V)	22 kW
Motor power (440V)	22 kW

ADDITIONAL SPECIFICATIONS

Physical interface	RS485
Rated supply voltage	230-440 V
Discrete input number	3
Communication protocol	Modbus
Discrete input voltage	24 V
Discrete output number	2
Control circuit voltage	230 V
IP degree of protection	IP20
Manufacturer part number	ATS22D47Q
Control circuit consumption	20 W

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.