

ATS22C14Q

Schneider Electric ATS22C14Q - Altistart 22 Soft Starter for Asynchronous Motors

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	ATS22C14Q
PRODUCT FAMILY	CATEGORY
Altistart 22	Soft Starter
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

This Altistart 22 soft starter can feed 3-phase asynchronous motors in supply line or delta connection. It has a rating of 140A and 230V to 440V, a rated power up to 75kW (400V to 440V in supply line) and up to 110kW (400V to 440V in motor delta connection). It is designed for simple and complex machines such as centrifugal and piston pumps, fans, screw compressors and material handling equipment. Slim form factor improves versatility; allows mounting in frames of any kind of machines. It features an Integrated bypass, this reduces noise and decreases heat dissipation. Compatibility with SoMove software allows configurations and settings to be easily transferred, meaning spares can be quickly installed. It provides smooth starting for your machinery, avoiding mechanical stresses and extending their service life. Schneider Electric ATS22C14Q is the exact manufacturer reference for Altistart 22 Soft Starter for Asynchronous Motors in the Altistart 22 family. Recorded technical characteristics include Depth: 229.5 mm; Width: 150 mm; Height: 356 mm; Net weight: 18 kg; Supply frequency: 50...60 Hz; IcL starter rating: 140 A; Motor power (230V): 37 kW; Motor power (400V): 75 kW. For an RFQ, use the complete part number ATS22C14Q so the required rating, configuration and compatible accessories remain exact. Review the linked manufacturer data sheet against the supply system, load, enclosure, environmental conditions and applicable standards before final engineering selection. This I

RECORDED SPECIFICATIONS

Depth	229.5 mm
Width	150 mm
Height	356 mm
Net weight	18 kg
Supply frequency	50...60 Hz
IcL starter rating	140 A
Motor power (230V)	37 kW
Motor power (400V)	75 kW
Motor power (440V)	75 kW
Rated supply voltage	230...440 V

ADDITIONAL SPECIFICATIONS

Communication protocol	Modbus
Control circuit voltage	230 V
Factory setting current	131 A
IP degree of protection	IP00
Manufacturer part number	ATS22C14Q
Network number of phases	3 phases

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.