

ATS22C32Q

Altistart 22 Soft Starter ATS22C32Q

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	ATS22C32Q
PRODUCT FAMILY	CATEGORY
Altistart 22	Soft Starter
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

This Altistart 22 soft starter can feed 3-phase asynchronous motors in supply line or delta connection. It has a rating of 320A and 230V to 440V, a rated power up to 160kW (400V to 440V in supply line) and up to 250kW (400V to 440V in motor delta connection). It is designed for simple and complex machines such as centrifugal and piston pumps, fans, screw compressors and material handling equipment. Slim form factor improves versatility; allows mounting in frames of any kind of machines. It features an Integrated bypass, this reduces noise and decreases heat dissipation. Compatibility with SoMove software allows configurations and settings to be easily transferred, meaning spares can be quickly installed. It provides smooth starting for your machinery, avoiding mechanical stresses and extending their service life. Schneider Electric ATS22C32Q is the exact manufacturer reference for Altistart 22 Soft Starter ATS22C32Q in the Altistart 22 family. Recorded technical characteristics include Depth: 299 mm; Width: 206 mm; Height: 425 mm; Phases: 3; Net weight: 33 kg; IP protection: IP00; Rated current: 320 A; Certifications: UL, CCC, C-Tick, CSA, GOST. For an RFQ, use the complete part number ATS22C32Q so the required rating, configuration and compatible accessories remain exact. Review the linked manufacturer data sheet against the supply system, load, enclosure, environmental conditions and applicable standards before final engineering selection. This listing is intended for proje

RECORDED SPECIFICATIONS

Depth	299 mm
Width	206 mm
Height	425 mm
Phases	3
Net weight	33 kg
IP protection	IP00
Rated current	320 A
Certifications	UL, CCC, C-Tick, CSA, GOST
Discrete inputs	3
Discrete outputs	2

ADDITIONAL SPECIFICATIONS

Supply frequency	50...60 Hz
Motor power (230V)	90 kW
Motor power (400V)	160 kW
Motor power (440V)	160 kW
Rated supply voltage	230...440 V
Operating temperature	-10?40 °C
Communication protocol	Modbus
Control circuit voltage	230 V
Manufacturer part number	ATS22C32Q

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.