

7PV1508-1AW30

|                |                                   |                                |                          |
|----------------|-----------------------------------|--------------------------------|--------------------------|
| BRAND          | Siemens                           | ORDER CODE / PRODUCT REFERENCE | 7PV1508-1AW30            |
| PRODUCT FAMILY | SIRIUS                            | CATEGORY                       | Industrial Relay         |
| SUPPLY BASIS   | RFQ / on request - no stock claim | RECORD IDENTITY                | Catalog identity matched |

PRODUCT DESCRIPTION

Timing relay, electronic Multifunction 1 change-over contact, 7 functions 7 time ranges 0.05 s ... 100 h 12-240 V AC/DC with LED, Screw terminal Siemens 7PV1508-1AW30 is the exact orderable reference for Timing relay, electronic Multifunction 1 change-over contact, 7 functions 7 time ranges 0.05 s ... 100 h 12-240 V AC/DC with LED, Screw terminal and has been verified as an active product on Siemens Industry Mall. It belongs to Product Lifecycle (PLM) PM300:Active Product Price data Price Group 41H List Price Show prices. Recorded manufacturer technical characteristics include Contacts: 1 change-over; Functions: 7 (Multifunction); IP Protection: IP20; Recovery time: 500 ms; Terminal type: Screw; Min. ON period: 35 ms; Adjustable time: 0.05 s to 100 h (7 ranges); Repeat accuracy: 2 %. For an RFQ, use the complete part number so the required electrical rating, hardware revision and compatible accessories remain exact. The linked Siemens data sheet should be checked against the application, supply system, environmental conditions and applicable standards before final engineering selection.

RECORDED SPECIFICATIONS

|                 |                            |
|-----------------|----------------------------|
| Contacts        | 1 change-over              |
| Functions       | 7 (Multifunction)          |
| Coil voltage    | 12-240 V AC                |
| Product type    | Industrial Relay           |
| IP Protection   | IP20                       |
| Recovery time   | 500 ms                     |
| Terminal type   | Screw                      |
| Min. ON period  | 35 ms                      |
| Adjustable time | 0.05 s to 100 h (7 ranges) |
| Repeat accuracy | 2 %                        |

ADDITIONAL SPECIFICATIONS

|                                    |                                                  |
|------------------------------------|--------------------------------------------------|
| Setting accuracy                   | 5 %                                              |
| Insulation voltage                 | 300 V                                            |
| Official lifecycle                 | Current official manufacturer lifecycle evidence |
| Overload relay type                | Electronic                                       |
| Isolation test voltage             | 2.2 kV                                           |
| Mechanical service life            | 10,000,000 cycles                                |
| Manufacturer part number           | 7PV1508-1AW30                                    |
| Surge voltage resistance           | 4000 V                                           |
| Control supply voltage AC/DC       | 12-240 V                                         |
| Electrical endurance (AC-15, 230V) | 100,000 cycles                                   |

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.