

LC1D32M7

Schneider Electric LC1D32M7 - TeSys D contactor - 3P(3 NO) - AC-3 - <= 440 V 32 A - 220 V AC coil

|                                   |                                |
|-----------------------------------|--------------------------------|
| BRAND                             | ORDER CODE / PRODUCT REFERENCE |
| Schneider Electric                | LC1D32M7                       |
| PRODUCT FAMILY                    | CATEGORY                       |
| TeSys Deca                        | Contactor                      |
| SUPPLY BASIS                      | RECORD IDENTITY                |
| RFQ / on request - no stock claim | Catalog identity matched       |

PRODUCT DESCRIPTION

TeSys D contactor, 3 poles (3NO), for motor control applications up to 32A/690V AC-3/3e (15kW@400V). It provides a 220V 50/60Hz AC coil, 1NO+1NC built-in auxiliary contacts (NC mirror certified), connection by screw clamp terminals. For operating rates until 3600 cycles/hour and environments until 60°C, it procures high reliability and durability. Compact (45mm width), DIN-rail mounting or screw fixing. Multi standards certified (IEC, UL, CSA, CCC, EAC, Marine), Green Premium compliant (RoHS/REACH). Schneider Electric LC1D32M7 is the exact manufacturer reference for TeSys D contactor - 3P(3 NO) - AC-3 - <= 440 V 32 A - 220 V AC coil in the TeSys Deca family. Recorded technical characteristics include Poles: 3P; Rated current: 32 A; Mechanical durability: 15 Mcycles; Control circuit voltage: 220 V AC 50/60 Hz; Motor power (AC-3, 400V): 15 kW; Rated insulation voltage: 690 V; Rated operational voltage: <= 690 V AC, <= 300 V DC; Conventional thermal current: 50 A. For an RFQ, use the complete part number LC1D32M7 so the required rating, configuration and compatible accessories remain exact. Review the linked manufacturer data sheet against the supply system, load, enclosure, environmental conditions and applicable standards before final engineering selection. This listing is intended for project, maintenance and replacement enquiries across Egypt, GCC and the wider MENA region; it does not claim local stock.

RECORDED SPECIFICATIONS

|                              |                          |
|------------------------------|--------------------------|
| Poles                        | 3P                       |
| Rated current                | 32 A                     |
| Mechanical durability        | 15 Mcycles               |
| Control circuit voltage      | 220 V AC 50/60 Hz        |
| Manufacturer part number     | LC1D32M7                 |
| Motor power (AC-3, 400V)     | 15 kW                    |
| Rated insulation voltage     | 690 V                    |
| Rated operational voltage    | <= 690 V AC, <= 300 V DC |
| Conventional thermal current | 50 A                     |

**ADDITIONAL SPECIFICATIONS****MANUFACTURER DOCUMENTATION**

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.