

6EP4135-0GL00-0AY0

Siemens 6EP4135-0GL00-0AY0 - SITOP BAT1600 EX 24 V DC 12 Ah Pb battery module

|                |                                   |                                |                          |
|----------------|-----------------------------------|--------------------------------|--------------------------|
| BRAND          | Siemens                           | ORDER CODE / PRODUCT REFERENCE | 6EP4135-0GL00-0AY0       |
| PRODUCT FAMILY | SITOP BAT1600                     | CATEGORY                       | DC UPS Power Supply      |
| SUPPLY BASIS   | RFQ / on request - no stock claim | RECORD IDENTITY                | Catalog identity matched |

PRODUCT DESCRIPTION

SITOP BAT1600 EX 24 V DC 12 Ah Pb battery module with maintenance- free closed lead-acid battery for SITOP UPS1600  
Siemens 6EP4135-0GL00-0AY0 is the exact orderable reference for SITOP BAT1600 EX 24 V DC 12 Ah Pb battery module and has been verified as an active product on Siemens Industry Mall. It belongs to SITOP BAT1600 battery modules. Recorded manufacturer technical characteristics include Net weight: 10.2 kg; Peak current: 120 A (for 30 ms); Battery capacity: 12 Ah; IP protection class: IP20; Rated output current: 40 A; Operating temperature: -15 to +50 °C; Dimensions (W x H x D): 225 x 156 x 138 mm; Rated output voltage DC: 24 V. For an RFQ, use the complete part number so the required electrical rating, hardware revision and compatible accessories remain exact. The linked Siemens data sheet should be checked against the application, supply system, environmental conditions and applicable standards before final engineering selection.

RECORDED SPECIFICATIONS

|                         |                     |
|-------------------------|---------------------|
| Net weight              | 10.2 kg             |
| Coil voltage            | 24 V DC             |
| Peak current            | 120 A (for 30 ms)   |
| Product type            | DC UPS Power Supply |
| Battery capacity        | 12 Ah               |
| IP protection class     | IP20                |
| Rated output current    | 40 A                |
| Operating temperature   | -15 to +50 °C       |
| Dimensions (W x H x D)  | 225 x 156 x 138 mm  |
| Rated output voltage DC | 24 V                |

ADDITIONAL SPECIFICATIONS

|                          |                          |
|--------------------------|--------------------------|
| Service life (at 20°C)   | 4 years                  |
| Manufacturer part number | 6EP4135-0GL00-0AY0       |
| Maximum charging current | 3 A                      |
| Short-circuit protection | 50A / 32V Maxi flat fuse |

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.