

6AG1334-3BA10-7AA0

Siemens 6AG1334-3BA10-7AA0 - SIPLUS PS PSU200M 10A Stabilized Power Supply

|                |                                   |                                |                          |
|----------------|-----------------------------------|--------------------------------|--------------------------|
| BRAND          | Siemens                           | ORDER CODE / PRODUCT REFERENCE | 6AG1334-3BA10-7AA0       |
| PRODUCT FAMILY | SIPLUS PS                         | CATEGORY                       | Power Supply             |
| SUPPLY BASIS   | RFQ / on request - no stock claim | RECORD IDENTITY                | Catalog identity matched |

PRODUCT DESCRIPTION

SIPLUS PS PSU200M 10 A based on 6EP1334-3BA10 with conformal coating, -25?+70 °C, stabilized power supply input: 120/230-500 V AC output: 24 V/10 A DC Siemens 6AG1334-3BA10-7AA0 is the exact orderable reference for SIPLUS PS PSU200M 10A Stabilized Power Supply and has been verified as an active product on Siemens Industry Mall. It belongs to 1-phase and 2-phase, 24 V DC. Recorded manufacturer technical characteristics include Output power: 240 W; Input voltage: 120/230-500 V AC; Output voltage: 24 V DC; Rated line range: 47 ... 63 Hz; Conformal coating: Yes; Rated output current: 10 A; Operating temperature: -25...+70 °C; Built-in incoming fuse: T 6.3 A. For an RFQ, use the complete part number so the required electrical rating, hardware revision and compatible accessories remain exact. The linked Siemens data sheet should be checked against the application, supply system, environmental conditions and applicable standards before final engineering selection.

RECORDED SPECIFICATIONS

|                      |                  |
|----------------------|------------------|
| Coil voltage         | 230-500 V AC     |
| Output power         | 240 W            |
| Product type         | Power Supply     |
| Input voltage        | 120/230-500 V AC |
| Rated current        | 10 A             |
| Rated voltage        | 24 V             |
| Output voltage       | 24 V DC          |
| Rated line range     | 47 ... 63 Hz     |
| Conformal coating    | Yes              |
| Rated output current | 10 A             |

**ADDITIONAL SPECIFICATIONS**

|                                          |                        |
|------------------------------------------|------------------------|
| Operating temperature                    | -25...+70 °C           |
| Built-in incoming fuse                   | T 6.3 A                |
| Overvoltage resistance                   | 1300 V <sub>peak</sub> |
| Rated line frequency 1                   | 50 Hz                  |
| Rated line frequency 2                   | 60 Hz                  |
| Manufacturer part number                 | 6AG1334-3BA10-7AA0     |
| Mains buffering at Vin = 400 V           | 150 ms                 |
| Output voltage adjustment range          | 24 ... 28.8 V          |
| Mains buffering at Vin = 120/230 V, typ. | 150 ms                 |

**MANUFACTURER DOCUMENTATION**

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.