

5SU1354-7LB32

Siemens 5SU1354-7LB32 - SENTRON 5SU RCBO

BRAND	Siemens	ORDER CODE / PRODUCT REFERENCE	5SU1354-7LB32
PRODUCT FAMILY	SENTRON 5SU RCBO	CATEGORY	RCBO
SUPPLY BASIS	RFQ / on request - no stock claim	RECORD IDENTITY	Catalog identity matched

PRODUCT DESCRIPTION

Siemens 5SU1354-7LB32 RCBO from the SENTRON 5SU RCBO range. Official Siemens active listing: RCBO, 10 kA, 1P+N, type A, short-time-delayed G, super-resistant K, 30 mA, C-Char, In: 32 A, Un AC: 230 V. Key details: Voltage rating: AC 230 V, Breaking capacity: 10 kA, Poles: 1P+N, RCD type: A, Residual current: 30 mA, Trip curve: C, Rated current: 32 A. Selected for Egypt and Gulf residual-current protection demand, including distribution boards, commercial panels, industrial control panels, maintenance replacement, and OEM panel-building projects.

RECORDED SPECIFICATIONS

Poles	1P+N
RCD type	A
Trip curve	C
Product type	RCBO
Rated current	32 A
Rated voltage	230 V
Voltage rating	AC 230 V
Residual current	30 mA
Breaking capacity	10 kA

Siemens family path

ADDITIONAL SPECIFICATIONS

Manufacturer order code	5SU1354-7LB32
Manufacturer part number	5SU1354-7LB32
Official Siemens listing	

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.