

ACS480-04-05A7-4+K475

ABB ACS480-04-05A7-4+K475 - ABB ACS480-04-05A7-4 ACS480 drive with 2-port multiprotocol Ethernet

|                |                                   |                                |                          |
|----------------|-----------------------------------|--------------------------------|--------------------------|
| BRAND          | ABB                               | ORDER CODE / PRODUCT REFERENCE | 3AXD50000047768          |
| PRODUCT FAMILY | ACS480                            | CATEGORY                       | Variable Frequency Drive |
| SUPPLY BASIS   | RFQ / on request - no stock claim | RECORD IDENTITY                | Catalog identity matched |

PRODUCT DESCRIPTION

ABB ACS480-04-05A7-4+K475 is an active ACS480 general-purpose drive rated 380-480 V AC, three-phase, factory configured with 2-port multiprotocol Ethernet communication (FENA-21: EtherNet/IP, Modbus TCP and PROFINET). It is suitable for pumps, fans, compressors, conveyors and OEM control panels requiring direct PLC or industrial-network integration. The selected ABB plus-code is included in the order reference for accurate Egypt and MENA quotation.

RECORDED SPECIFICATIONS

|                    |                                               |
|--------------------|-----------------------------------------------|
| Supply             | 380-480 V AC, three-phase                     |
| Drive class        | General-purpose drive                         |
| Drive family       | ACS480                                        |
| Adapter module     | FENA-21: EtherNet/IP, Modbus TCP and PROFINET |
| ABB option code    | +K475                                         |
| Fieldbus option    | 2-port multiprotocol Ethernet                 |
| Lifecycle basis    | Current ABB ACS480 catalog                    |
| Region selection   | Egypt and MENA demand-weighted                |
| ABB ordering code  | 3AXD50000047768                               |
| Configuration type | Factory-orderable single fieldbus option      |

ADDITIONAL SPECIFICATIONS

|                        |        |
|------------------------|--------|
| Heavy-duty current     | 4 A    |
| Light-duty current     | 5.3 A  |
| Heavy-duty motor power | 1.5 kW |
| Light-duty motor power | 2.2 kW |

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.