

XB4BVM3

Harmony XB4 XB4BVM3 green LED pilot light 22 mm 230...240 V AC

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	XB4BVM3
PRODUCT FAMILY	CATEGORY
Harmony XB4	Pilot Light
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

The Schneider Electric XB4BVM3 is a complete Harmony XB4 pilot light with a chromium plated metal bezel, plain green lens and integral universal LED supplied directly at 230...240 V AC 50/60 Hz, mounted in the standard 22.5 mm panel cut-out. The XB4BVM3 draws 14 mA, is rated 250 V insulation voltage and 4 kV impulse withstand, offers an LED service life of 100,000 h at rated voltage and 25 degrees C, and connects through screw clamp terminals marked X1-X2. The unit is sealed to IP66, IP67, IP69 and IP69K and works from -40 to 70 degrees C. Because most Egyptian and Gulf control panels run their indication circuits directly at 230 V AC, the XB4BVM3 is the standard running or healthy indicator on motor starters, pump and compressor control panels, water treatment plants, cement and textile lines and food and beverage machinery. Request a quote for the Schneider Electric XB4BVM3.

RECORDED SPECIFICATIONS

Light source	Universal LED, integral LED, with plain lens
Service life	100000 h at rated voltage and 25 °C
Bezel material	Chromium plated metal
Product weight	0.08 kg
Range of product	Harmony XB4
Mounting diameter	22.5 mm
Official lifecycle	Current official manufacturer lifecycle evidence
Current consumption	14 mA
Terminals description	ISO n°1 (X1-X2)PL
Dimensions (H x W x D)	47 mm x 30 mm x 54 mm

ADDITIONAL SPECIFICATIONS

IP degree of protection	IP66 conforming to IEC 60529, IP67, IP69, IP69K
Manufacturer part number	XB4BVM3
Product or component type	Pilot light
[Us] rated supply voltage	230...240 V AC 50/60 Hz
Cap/operator or lens colour	Green
Ambient air temperature for operation	-40...70 °C
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.