

GV3P13

TeSys Deca GV3 motor circuit breaker GV3P13 13 A

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	GV3P13
PRODUCT FAMILY	CATEGORY
TeSys Deca	Motor circuit breaker
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

The Schneider Electric GV3P13 is a robust 3-pole thermal-magnetic motor circuit breaker from the TeSys Deca range, engineered for reliable motor protection in demanding industrial environments. Designed for AC networks operating at 50/60 Hz, this GV3P13 unit provides a rated current of 13 A with a thermal protection adjustment range of 9 to 13 A. Its high breaking capacity, notably 100 kA Icu at 400/415 V AC, ensures superior fault protection, while it supports motor power up to 5.5 kW at 400/415 V. Featuring a user-friendly rotary handle and EverLink terminals for secure wiring, this device also offers phase failure sensitivity and suitability for isolation. It is an excellent choice for critical applications in Egypt and the Gulf, including motor control in cement plants, oil and gas facilities, water treatment, food and beverage production, textile manufacturing, and building services. Contact us today to request a quote for this essential Schneider Electric motor protection solution.

RECORDED SPECIFICATIONS

Depth	136 mm
Width	55 mm
Height	132 mm
Control type	Rotary handle
Network type	AC
Product weight	0.96 kg
Network frequency	50/60 Hz
Poles description	3P
Tightening torque	5 N.m - on screw clamp terminal
Official lifecycle	Current official manufacturer lifecycle evidence

ADDITIONAL SPECIFICATIONS

[In] rated current	13 A
IP degree of protection	IP20
Manufacturer part number	GV3P13
Magnetic tripping current	182 A
Phase failure sensitivity	Yes conforming to IEC 60947-4-1
Suitability for isolation	Yes conforming to IEC 60947-1
[Ue] rated operational voltage	690 V AC 50/60 Hz
Thermal protection adjustment range	9?13 A
Ambient air temperature for operation	-20?60 °C
Motor power kW (at 400/415 V AC 50/60 Hz)	5.5 kW
Breaking capacity (at 400/415 V AC 50/60 Hz)	100 kA Icu

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.