

GV3P32

TeSys GV3 Motor Circuit Breaker GV3P32

|                                   |                                |
|-----------------------------------|--------------------------------|
| BRAND                             | ORDER CODE / PRODUCT REFERENCE |
| Schneider Electric                | GV3P32                         |
| PRODUCT FAMILY                    | CATEGORY                       |
| TeSys Deca                        | Motor Circuit Breaker          |
| SUPPLY BASIS                      | RECORD IDENTITY                |
| RFQ / on request - no stock claim | Catalog identity matched       |

PRODUCT DESCRIPTION

The Schneider Electric TeSys GV3P32 Motor Circuit Breaker delivers robust and reliable thermal-magnetic protection for medium and large AC motors in demanding industrial environments. Part of the acclaimed TeSys Deca range, this GV3P series breaker is engineered with a 3P configuration and a 32 A rated current, featuring an adjustable thermal protection range of 23?32 A and a magnetic tripping current of 448 A. It boasts an impressive breaking capacity of 100 kA Icu at 400/415 V AC 50/60 Hz, making it suitable for motor power up to 15 kW at these common regional voltages. Equipped with a user-friendly rotary handle and innovative EverLink terminals, the Schneider Electric GV3P32 ensures secure and simplified wiring. Its IP20 protection rating and -20?60 °C operational temperature range guarantee performance even in harsh conditions. Ideal for critical applications across Egypt and the Gulf, including cement plants, oil and gas facilities, water treatment plants, food and beverage processing, and building services, this motor circuit breaker is designed for both 35 mm DIN rail and panel mounting. Contact us today to request a comprehensive quote for your Schneider Electric GV3P32 requirements.

RECORDED SPECIFICATIONS

|                |                                                                          |
|----------------|--------------------------------------------------------------------------|
| Depth          | 136 mm                                                                   |
| Width          | 55 mm                                                                    |
| Height         | 132 mm                                                                   |
| Standards      | EN/IEC 60947-2, EN/IEC 60947-4-1                                         |
| Terminals      | EverLink terminals                                                       |
| Fixing mode    | 35 mm symmetrical DIN rail: clipped; Panel: screwed (with 3 x M4 screws) |
| Control type   | Rotary handle                                                            |
| Network type   | AC                                                                       |
| Motor power kW | 15 kW at 400/415 V AC 50/60 Hz                                           |
| Product weight | 0.96 kg                                                                  |

ADDITIONAL SPECIFICATIONS

|                                       |                                                               |
|---------------------------------------|---------------------------------------------------------------|
| Breaking capacity                     | 100 kA Icu at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 |
| Network frequency                     | 50/60 Hz                                                      |
| Poles description                     | 3P                                                            |
| Official lifecycle                    | Current official manufacturer lifecycle evidence              |
| [In] rated current                    | 32 A                                                          |
| IP degree of protection               | IP20 conforming to IEC 60529                                  |
| Manufacturer part number              | GV3P32                                                        |
| Magnetic tripping current             | 448 A                                                         |
| [Ue] rated operational voltage        | 690 V AC 50/60 Hz conforming to IEC 60947-2                   |
| Thermal protection adjustment range   | 23?32 A conforming to IEC 60947-2                             |
| Ambient air temperature for operation | -20?60 °C                                                     |

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.