

GV3P65

Schneider Electric GV3P65 - TeSys Deca GV3 Motor Circuit Breaker 65 A

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	GV3P65
PRODUCT FAMILY	CATEGORY
TeSys Deca	Motor Circuit Breaker
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

The Schneider Electric GV3P65 is a robust 3-pole TeSys GV3 motor circuit breaker from the TeSys Deca range, engineered for reliable motor protection in industrial environments. This thermal-magnetic protection device is designed to safeguard medium and large AC motors up to 65 A, featuring a high breaking capacity of 50 kA at 400/415 V AC 50/60 Hz. With a thermal protection adjustment range of 48 to 65 A and a rated operational voltage up to 690 V, it provides comprehensive overload and short-circuit protection, including phase failure sensitivity. Equipped with a user-friendly rotary handle and secure EverLink terminals, the GV3P65 ensures safe and efficient operation. Its compact design (55 mm width) allows for versatile mounting on both DIN rail and panels. This breaker is ideal for demanding applications across the Middle East and Gulf regions, commonly found in critical sectors such as oil and gas, water treatment, cement manufacturing, food and beverage processing, textiles, and building services. For comprehensive motor control and protection solutions, request a quote for the Schneider Electric GV3P65 today.

RECORDED SPECIFICATIONS

Depth	136 mm
Width	55 mm
Height	132 mm
Control type	Rotary handle
Network type	AC
Mounting mode	DIN rail / Panel mounted
Motor power kW	30 kW at 400/415 V AC 50/60 Hz
Product weight	0.96 kg
Network frequency	50/60 Hz
Poles description	3P

ADDITIONAL SPECIFICATIONS

Official lifecycle	Current official manufacturer lifecycle evidence
Rated current (In)	65 A
Breaking capacity (Icu)	50 kA at 400/415 V AC 50/60 Hz
IK degree of protection	IK09 enclosure
IP degree of protection	IP20
Manufacturer part number	GV3P65
Phase failure sensitivity	Yes
Suitability for isolation	Yes
Rated operational voltage (Ue)	690 V AC 50/60 Hz
Thermal protection adjustment range	48?65 A

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.