

A9F73202

Schneider Electric A9F73202 - Acti9 iC60N 2P 2A B-curve Miniature Circuit Breaker

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	A9F73202
PRODUCT FAMILY	CATEGORY
Acti9	Miniature Circuit Breaker
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

The Schneider Electric A9F73202 is a robust Acti9 iC60N Miniature Circuit Breaker (MCB) designed for efficient and reliable protection of final distribution circuits. This 2-pole device features a 2 A rated current and a B-curve trip characteristic, making it ideal for safeguarding resistive or lightly inductive loads against overcurrents and short circuits. Engineered with thermal-magnetic trip unit technology, it offers both overload and short-circuit protection for AC and DC networks. The Schneider Electric A9F73202 boasts impressive breaking capacities of 6000 A (IEC/EN 60898-1 at 400 V AC) and 50 kA (IEC/EN 60947-2 at 380-415 V AC), ensuring high performance in demanding environments. Its broad operational voltage compatibility, including 220-240 V AC and 380-415 V AC at 50/60 Hz, aligns perfectly with electrical standards in Egypt and the Gulf region. This MCB is suitable for a wide array of applications, from building services to critical industrial sectors such as cement, oil and gas, water treatment, food and beverage, and textiles. Featuring DIN rail mounting and an IP20 degree of protection, it ensures straightforward installation and durability. Request a quote today for the Schneider Electric A9F73202 to secure your electrical installations.

RECORDED SPECIFICATIONS

Width	36 mm
Curve code	B
Network type	AC, DC
Product weight	0.25 kg
Mounting support	35 mm DIN rail
Network frequency	50/60 Hz
Poles description	2P
Terminal capacity	1?25 mm² rigid; 1?16 mm² flexible
Official lifecycle	Current official manufacturer lifecycle evidence
[In] rated current	2 A

ADDITIONAL SPECIFICATIONS

Trip unit technology	Thermal-magnetic
Breaking capacity (DC)	10 kA Icu at <= 125 V DC
IP degree of protection	IP20
Manufacturer part number	A9F73202
Number of protected poles	2
Suitability for isolation	Yes
[Ue] rated operational voltage	
Breaking capacity (IEC/EN 60898-1)	6000 A Icn at 400 V AC 50/60 Hz
Breaking capacity (IEC/EN 60947-2)	50 kA Icu at 380...415 V AC 50/60 Hz
Ambient air temperature for operation	-35?70 °C

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.