

XB4BD53

Schneider Electric XB4BD53 Selector Switch, 3-Position, Spring Return, 2 NO

BRAND	ORDER CODE / PRODUCT REFERENCE
Schneider Electric	XB4BD53
PRODUCT FAMILY	CATEGORY
Harmony XB4	Selector Switch
SUPPLY BASIS	RECORD IDENTITY
RFQ / on request - no stock claim	Catalog identity matched

PRODUCT DESCRIPTION

The Schneider Electric XB4BD53 is a robust Harmony XB4 series selector switch, engineered for reliable control in demanding industrial environments. This complete product features a durable chromium-plated metal bezel and a 22.5 mm mounting diameter, making it ideal for integration into control panels. The XB4BD53 selector switch offers a 3-position operation with a "to centre" spring return, ensuring precise control and ease of use. It is equipped with two normally open (2 NO) slow-break contacts, providing clear circuit control. Connectivity is secure and straightforward with screw clamp terminals, accommodating up to 2 x 1.5 mm² cables. With an IP69/IP69K/IP67 degree of protection and an operating temperature range of -40 to 70 °C, the XB4BD53 is built to withstand harsh conditions. Rated for 3 A at 240 V AC-15 and 0.27 A at 250 V DC-13, this switch is well-suited for a wide array of control applications in Egyptian and Gulf industries such as machinery operation, mode selection, or system activation in cement plants, oil and gas facilities, water treatment, food and beverage processing, textiles, and building services. Its mechanical durability of 1,000,000 cycles ensures long-term performance. Contact us to request a quote for the Schneider Electric XB4BD53 selector switch and enhance your control systems.

RECORDED SPECIFICATIONS

Standards	
Bezel material	Chromium plated metal
Product weight	0.105 kg
Operator profile	Black standard handle
Type of operator	To centre spring return
Contact operation	Slow-break
Mounting diameter	22.5 mm
Official lifecycle	Current official manufacturer lifecycle evidence
Mechanical durability	1000000 cycles
Product certifications	BV; UL; CSA; DNV; LROS (Lloyds register of shipping)

ADDITIONAL SPECIFICATIONS

Connections - terminals	Screw clamp terminals, <= 2 x 1.5 mm² with cable end conforming to IEC 60947-1
IP degree of protection	IP69; IP69K; IP67 conforming to IEC 60529
Manufacturer part number	XB4BD53
Product or component type	Selector switch
Contacts type and composition	2 NO
Operator position information	3 positions +/- 45°
[Ui] rated insulation voltage	600 V (pollution degree 3) conforming to IEC 60947-1
[Ie] rated operational current	
Ambient air temperature for operation	-40?70 °C

MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.