# ATV340D11N4

## Schneider Electric ATV340D11N4 - Variable speed drive, Altivar Machine ATV340, 11 kW Heavy Duty, 400 V, 3 phases

**BRAND**
Schneider Electric

**PRODUCT FAMILY**
Altivar Machine ATV340

**SUPPLY BASIS**
RFQ / on request - no stock claim

**ORDER CODE / PRODUCT REFERENCE**
ATV340D11N4

**CATEGORY**
VFD

**RECORD IDENTITY**
Catalog identity matched

### PRODUCT DESCRIPTION

This Altivar 340 variable speed drive can feed 3-phase synchronous and asynchronous motors in open and closed loop control. Altivar Machine ATV340 drives are sized heavy duty as standard. It works at a rated power up to 11kW / 15hp and a rated voltage from 380V to 480V AC. ATV340 has been designed to meet the needs of applications for harsh environments, such as vibration, shock and non-conductive dust and where high temperature resistance up to 60 °C is needed. This product integrates Modbus serial line communication protocols as standard. it weighs 9.5kg and its dimensions are, 180mm wide, 385mm high, 249mm deep. ATV340 incorporates functions and features suitable for the most common applications, including packaging, material handling, material working, hoisting. It conforms to international standards IEC/EN 61800-5-1 and IEC/EN 61800-3 (immunity and conducted and radiated EMC emissions), IEC 60721-3, IEC 61508, IEC 13849-1. It is also CE, UL, CSA, and TÜV certified. Accessories and options (encoder interface modules, I/O expansion modules, communication modules, braking resistors, line chokes, additional EMC filters) are available with Altivar Machine ATV340 drives, depending on the drive rating. It is designed to be mounted in vertical position (+/- 10 °) on a panel, thanks to 4 fixing holes. It is fully integrated inside Schneider Electric?s EcoStruxure Machine through DTM. It is possible to configure, control, and diagnose ATV340 drives directly in SoMachine and SoMove

### RECORDED SPECIFICATIONS

| | |
|---|---|
| **EMC filter** | Class C3 integrated |
| **Supply frequency** | 50...60 Hz |
| **Rated supply voltage** | 380...480 V |
| **Maximum input current** | 34.7 A |
| **Maximum output voltage** | 480 V |
| **Nominal output current** | 24.0 A |
| **IP degree of protection** | IP20 |
| **Manufacturer part number** | ATV340D11N4 |
| **Maximum output frequency** | 0.599 KHz |
| **Motor power (heavy duty)** | 11 KW |

## ADDITIONAL SPECIFICATIONS

| | |
|---|---|
| **Network number of phases** | 3 phases |
| **Motor power (normal duty)** | 15 KW |
| **Communication port protocol** | Modbus serial |
| **Nominal switching frequency** | 4 kHz |

## MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.