# ATV320U11M2W

## Schneider Electric ATV320U11M2W - Variable speed drive, Altivar Machine ATV320, 1.1 kW, 200...240 V, 1 phase, enclosed

**BRAND**
Schneider Electric

**PRODUCT FAMILY**
Altivar Machine ATV320

**SUPPLY BASIS**
RFQ / on request - no stock claim

**ORDER CODE / PRODUCT REFERENCE**
ATV320U11M2W

**CATEGORY**
VFD

**RECORD IDENTITY**
Catalog identity matched

### PRODUCT DESCRIPTION

Altivar Machine ATV320 range is an offer of variable speed drives designed for Original Equipment Manufacturers (OEMs). This ATV320 drive can feed single-phase synchronous and asynchronous motors. It works at a rated power up to 1.1kW, and a rated voltage from 200V to 240V. Altivar high IP offers washable drives for harsh environments, if users want to clean the dust and chemical pollution outside of drives. It is delivered without fan, with embedded EMC C2 filter and it provides IP66 protection. It integrates as standard Modbus and CANopen communication protocols with access via the RJ45 connector on the front of the drive. It weighs 7.4kg. The drive software includes 5 safety functions that help machines meet safety requirements. These safety functions are configured using SoMove software. This Altivar Machine ATV320 is designed for conveyors, carton packers, gantry cranes, woodworking, metal processing, fans, Food & Beverage industry. It conforms to IEC, UL, TUV, KC and other international standards. EcoStruxure Machine software compatibility enables developping, configuring and commissioning the entire machine in a single software environment, including logic, motion control, HMI and related network automation functions. It is delivered in 2 packages. ATV320 can be installed alone or side by side in a multi-drive configuration. The Altivar Machine ATV320 series focus on easy integration for simple and advanced machine requirements with proven motor control and connectivit

### RECORDED SPECIFICATIONS

| | |
|---|---|
| **Width** | 250 mm |
| **Height** | 340 mm |
| **Motor power** | 1.1 kW |
| **Line current** | 13.7 A at 200 V |
| **Apparent power** | 2.8 kVA at 240 V |
| **Analogue inputs** | 3 |
| **Discrete inputs** | 7 |
| **Analogue outputs** | 1 |
| **Discrete outputs** | 3 |
| **EMC filter class** | Class C2 |

## ADDITIONAL SPECIFICATIONS

| | |
|---|---|
| **Network frequency** | 50...60 Hz |
| **Power dissipation** | 61 W at 200 V |
| **Switching frequency** | 2...16 kHz adjustable |
| **Rated supply voltage** | 200...240 V |
| **Maximum input current** | 13.7 A |
| **Maximum output voltage** | 240 V |
| **Nominal output current** | 6.9 A |
| **IP degree of protection** | IP66 |
| **Manufacturer part number** | ATV320U11M2W |
| **Maximum output frequency** | 0.599 kHz |
| **Nominal switching frequency** | 4 kHz |
| **Safety function Safe Stop 1 (SS1)** | True |
| **Safety function Safe Torque Off (STO)** | True |
| **Safety function Safely Limited Speed (SLS)** | True |

## MANUFACTURER DOCUMENTATION

No manufacturer document is linked because exact-SKU or compatible-family evidence has not been recorded.

Document status: This is an InduMarket product specification summary, not a manufacturer-issued datasheet. It is generated from the catalog record for the exact part number. Any linked manufacturer document passed the SKU-compatibility evidence gate. Confirm ratings, compatibility, certifications and any successor reference before ordering.